



Vinyl lettering and decal application guide:

- 1)** Application should not be attempted at temperatures below 12 degrees Celsius.
- 2)** Clean off surfaces thoroughly with surface cleaner; wipe the surface dry with a clean dry lint free cloth, special care must be taken to remove all traces of silicone polish.
- 3)** At this stage it can be helpful to mark the centre and draw a base line on the decal; care must be taken as the letters with a round base descend below the base line.
- 4)** Place a small piece of masking tape at each end of the decal and position it on the surface without removing any of the backing paper.
- 5)** Measurements can then be taken and the position adjusted to make the decal central and level, then take a step back and check that it looks straight and good. Adjust if necessary.
- 6)** Next place a strip of masking tape all the way across the top of the decal, half on the decal and half on the surface that you are applying to and remove the two small pieces of masking tape.
- 7)** Lift the bottom of the decal allowing it to hinge on the masking tape and carefully remove the backing paper, then holding the decal away from the surface, starting in the middle, squeegee it onto the surface using moderate pressure and smooth even strokes to the left and right ensuring that there are no wrinkles in the decal or application tape.
- 8)** Carefully remove the application tape and admire your handiwork.
- 9)** It is not uncommon to have some small air bubbles under the decal; these will disappear within a few weeks. Larger bubbles can be removed by carefully piercing the edge of the bubble with a needle and applying pressure with your thumb.

You are FINISHED!!! Any questions please contact us at:

support@michaelmurraysigns.ltd.uk

www.michaelmurraysigns.ltd.uk